

## Technical data

### COATINGS Endless-Coatings “Polyurethane Qualities”

## Endless rubber coatings on flat, timing and poly-V-belts

### Qualities: Polyurethane rubbers

Type	PUR white	PUR clear green	PUR black	PUR natural*	PUR green	PUR grey	PUR natural
Quality of rubber	Polyurethane 30 ShA	Polyurethane 40 ShA	Polyurethane 50 ShA	Polyurethane 60 ShA	Polyurethane 70 ShA	Polyurethane 80 ShA	Polyurethane 90 ShA
Properties	antistatic high friction wear resistant	antistatic high friction wear resistant	antistatic high friction high wear resistance	*FDA hydrolysis resistant	antistatic highest wear resistance	antistatic highest wear resistance	antistatic highest wear resistance
Temperature resistance	80 °C	80 °C	80 °C	80 °C	80 °C	80 °C	80 °C

## Produced dimensions

Length	150 – 1999 mm	+/- 1 %
Width	max. 280 mm	+/- 1 mm
Thickness	0.5 – 12.0 mm	+/- 0.1 mm

## Speciality

The coatings are truly endless, without any joint – no seam or splice! **These Polyurethane rubbers are available for projects with higher quantities only.**

The surface of the coating is grinded.

On request we can work the coating, for example with cross grooves, longitudinal grooves, vacuum holes, etc.

## Timing- and poly-V-belts supply


Normally we receive from our customer timing- and poly-V-belts in sleeves of minimum 200 mm width. The coated sleeves will be cut by us to the requested belt width.

## Technical data



### COATINGS Endless-Coatings "Polyurethane Qualities"

#### Boring, milling and further processing



Vacuum holes cylindrical




Vacuum holes conical





Vacuum holes with oval millings





Vacuum holes with cross millings





Vacuum holes with diagonal millings




Grooves cross



Grooves diagonal



Grooves longitudinal for pull-out



Self-tracking -guides

