

Technical data
COATINGS Endless-Coatings
Endless rubber coatings on flat, timing and poly-V-belts
Qualities: Rubber, Silicone and Natural caoutchouc

Type	CR black	NBR white*	NBR blue or light grey	XNBR light beige	EPDM green*	SI l' grey* or blue* transpa.*	NR red or white*	NR maroon
Quality of rubber	Chloroprene 70 ShA	Nitrile 65 ShA	Nitrile 75 ShA	Nitrile 75 ShA	EPDM 65 ShA	Silicone 40 ShA 30 ShA	Natural 40 ShA	Natural 50 ShA
Properties	antistatic, oil/grease-resistant	*FDA, wear-resistant	oil/grease and wear-resistant	very high wear resistance	*FDA, UV- and ozone-proof	*FDA non-stick	*FDA highest coefficient of friction	high coefficient of friction
Temperature resistance	100 °C	80 °C	80 °C	100 °C	120 °C	150 °C	60 °C	60 °C

Produced dimensions

Length	150 – 1999 mm	2000 – 9000 mm	+/- 1 %
Width	max. 280 mm	max. 280 mm	+/- 1 mm
Thickness	0.5 – 12.0 mm	1.0 – 8.0 mm	+/- 0.1 mm

Speciality

The coatings are truly endless, without any joint – no seam or splice!

The surface of the coating is grinded.

On request we can work the coating, for example with cross grooves, longitudinal grooves, vacuum holes, etc.

Timing- and poly-V-belts supply



Normally we receive from our customer timing- and poly-V-belts in sleeves of minimum 200 mm width. The coated sleeves will be cut by us to the requested belt width.

Technical data



COATINGS Endless-Coatings

Boring, milling and further processing



Vacuum holes cylindrical




Vacuum holes conical





Vacuum holes with oval millings





Vacuum holes with cross millings





Vacuum holes with diagonal millings





Grooves cross



Grooves diagonal



Grooves longitudinal for pull-out



Self-tracking -guides

