

### OVERVIEW

#### Graf-belts and endless-coatings

<b>HEVALOID®</b> Type 5005 spec.  Sample Collection 2	<b>Light power transmission and conveying belt, smooth / profiled</b> Endless woven, highly flexible and length-stable  <b>Thickness</b> 0.5 – 1.5 mm <b>Length</b> up to 1500 mm <b>Use:</b> light power transmission, paper folding, ATM and ticketing
<b>HEVALOID®</b> Type 535  Sample Collection 2	<b>Heavy power transmission and conveying belt</b> Endless woven, highly flexible and length-stable  <b>Thickness</b> 2.0 mm <b>Length</b> up to 9000 mm <b>Use:</b> textile-, wood- and metal processing machines, air ventilation
<b>Feeder belt</b> ECT 06 red with vacuum holes  Sample Collection 3	<b>High-performance vacuum feeder belt</b> Endless woven, high resistant to abrasion and highest friction  <b>Thickness</b> 1.5 mm – 12.0 mm <b>Length</b> up to 9000 mm <b>Use:</b> friction and vacuum feeders, letter sorting (POSTAL belts)
<b>CRELAST®</b> Crelast white (FDA) Crelast green Crelast black Sample Collection 4	<b>Elastic light conveying belt</b> Endless cured – no seam, no splice  <b>Thickness</b> 0.5 mm – 15.0 mm <b>Length</b> up to 2000 mm <b>Use:</b> digital printing, copying, ticketing, ATM, weighing belts (FDA)
<b>Roller / friction cover</b> Crelast EC red Crelast EC maroon Crelast blue Sample Collection 5	<b>Elastic friction and roller covers</b> Endless cured, highest resistant to abrasion and friction  <b>Thickness</b> 0.5 mm – 15.0 mm <b>Diameter inside</b> 10 mm to 600 mm <b>Use:</b> letter feeders, paper conveying – mounting without glue!
<b>HEVALOID®</b> Type 585 TW  Sample Collection 6 and 7	<b>Tube winder belts and Haul-off belts V 11095</b> Endless woven, highest resistant to abrasion and smooth run  <b>Thickness</b> 2.5 – 12.0 mm <b>Length</b> up to 9000 mm <b>Use:</b> tube winding; "haul-off" unit: wires, cables, caterpillars and plastic bags
<b>Endless coating</b> SI blue (FDA) coating on PU timing belt  Sample Collection 8	<b>Coatings – on flat, timing or Poly-V-belts</b> Endless coated – no splice, no seam  <b>Thickness</b> 0.5 mm – 12.0 mm <b>Length</b> up to 9000 mm <b>Use:</b> Haul-off units: wire, caterpillars and VFFS; feeders for paper and cardboard
<b>RONDLAST®</b> PU red 90 ShA (FDA)  Sample Collection 12	<b>High-performance round belts</b> Endless welded...super strong and reliable  <b>Thickness</b> 1.6 mm – 18 mm <b>Length</b> from 75 mm <b>Use:</b> drive for sorting and transportation plants; conveyors for food and packaging